

Cavity Wall

Available for cavity widths from 50mm to 165mm

OUTER LEAF

102mm

INNER LEAF

100mm



L6

To achieve loading figures lintel must be laterally restrained. Lintels may be propped to facilitate speed of construction.

Galvanised steel flange to outer leaf.


Extreme Load

L6/100

For cavity widths 90-105mm

Manufactured length (mm) to customer requirements	600-3000	3150-4800	5100	5400	5700	6000	6300	6600
Height 'h'	213	213	213	213	213	213	213	213
End Bearing	200	200	200	200	200	200	200	200
Total UDL kN	95	80	70	62	55	50	45	40

90-105mm cavity




L6/110

For cavity widths 110-125mm

Manufactured length (mm) to customer requirements	600-3000	3150-4800	5100	5400	5700	6000	6300	6600
Height 'h'	213	213	213	213	213	213	213	213
End Bearing	200	200	200	200	200	200	200	200
Total UDL kN	95	80	70	62	55	50	45	40

110-125mm cavity



L6/150

For cavity widths 150-165mm

Manufactured length (mm) to customer requirements	600-3000	3150-4800	5100	5400	5700	6000	6300	6600
Height 'h'	213	213	213	213	213	213	213	213
End Bearing	200	200	200	200	200	200	200	200
Total UDL kN	95	80	70	62	55	50	45	40

150-165mm cavity

