



IGAR

When low rise arches are required in brickwork above openings, the IG Universal Arch provides the ideal former for the bricklayer. Vacuum-formed from white pigmented impact resistant polystyrene.

Suitable for use in cavity walls and with timber frame construction, the unit is designed to sit on any steel lintel with an outer flange of 90mm to 95mm.

Universal Arch Selector

Opening Sizes	Nominal Arch Span	Arch Rise	Keystone Reference
450 – 500	475	75	IGAR 475
600 – 650	625	75	IGAR 625
650 – 700	675	75	IGAR 675
700 – 750	725	75	IGAR 725
800 – 850	825	75	IGAR 825
900 – 950	925	75	IGAR 925
1000 – 1050	1025	75	IGAR 1025
1100 – 1150	1125	75	IGAR 1125
1200 – 1250	1225	75	IGAR 1225
1300 – 1350	1325	75	IGAR 1325
1450 – 1500	1475	75	IGAR 1475
1500 – 1550	1525	75	IGAR 1525
1600 – 1650	1625	75	IGAR 1625
1650 – 1700	1675	75	IGAR 1675
1750 – 1800	1775	75	IGAR 1775
1900 – 1950	1925	150	IGAR 1925
1950 – 2000	1975	150	IGAR 1975
2100 – 2150	2125	150	IGAR 2125
2200 – 2250	2225	150	IGAR 2225
2300 – 2350	2325	150	IGAR 2325
2400 – 2450	2425	150	IGAR 2425
2550 – 2600	2575	150	IGAR 2575
2700 – 2750	2725	150	IGAR 2725